

## SECTION 1: IDENTIFICATION

### 1.1. Product Identifier

**Product Form:** Mixture

**Product Name:** Unleaded Gasoline

**Synonyms:** CountryMark 87 E10 Plus, 88 E15 Plus, CountryMark 89 E10 Plus, CountryMark 91 Plus, CountryMark 93 E10 Plus, 87 Regular, 87 Regular E10, 88 Regular E15, 89 Midgrade E10, 93 Premium E10, 84 CBOB, 91 CBOB, Hydrocarbon Mixture, Light Petroleum Distillate.

### 1.2. Intended Use of the Product

**Use of the substance/mixture:** No use is specified.

### 1.3. Name, Address, and Telephone of the Responsible Party

#### Company

Countrymark Refining and Logistics, LLC

1200 Refinery Road

Mt. Vernon, Indiana 47620

(812) 838-8165

[CountryMark.com](http://CountryMark.com)

### 1.4. Emergency Telephone Number

**Emergency Number** : Countrymark: (812) 838-8165 (CHEMTREC) (800) 424-9300

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the Substance or Mixture

#### Classification (GHS-US)

Flam. Liq. 1 H224

Skin Irrit. 2 H315

Muta. 1B H340

Carc. 1A H350

Repr. 2 H361

STOT SE 1 H370

STOT SE 3 H336

STOT RE 1 H372

Asp. Tox. 1 H304

Aquatic Acute 2 H401

Aquatic Chronic 2 H411

Full text of H-phrases: see section 16

### 2.2. Label Elements

#### GHS-US Labeling

#### Hazard Pictograms (GHS-US)



#### Signal Word (GHS-US)

: Danger

#### Hazard Statements (GHS-US)

: H224 - Extremely flammable liquid and vapor.  
 H304 - May be fatal if swallowed and enters airways.  
 H315 - Causes skin irritation.  
 H336 - May cause drowsiness or dizziness.  
 H340 - May cause genetic defects.  
 H350 - May cause cancer.  
 H361 - Suspected of damaging fertility or the unborn child.  
 H370 - Causes damage to organs.  
 H372 - Causes damage to organs through prolonged or repeated exposure.  
 H401 - Toxic to aquatic life.  
 H411 - Toxic to aquatic life with long lasting effects.

#### Precautionary Statements (GHS-US)

: P201 - Obtain special instructions before use.  
 P202 - Do not handle until all safety precautions have been read and understood.  
 P210 - Keep away from extremely high or low temperatures, ignition sources, and incompatible materials. No smoking.

# Unleaded Gasoline

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P233 - Keep container tightly closed.  
P240 - Ground/bond container and receiving equipment.  
P241 - Use explosion-proof electrical, ventilating, and lighting equipment.  
P242 - Use only non-sparking tools.  
P243 - Take precautionary measures against static discharge.  
P260 - Do not breathe vapors, mist, or spray.  
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.  
P270 - Do not eat, drink or smoke when using this product.  
P271 - Use only outdoors or in a well-ventilated area.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves, protective clothing, and eye protection.  
P301+P310 - If swallowed: Immediately call a poison center or doctor.  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.  
P308+P313 - If exposed or concerned: Get medical advice/attention.  
P314 - Get medical advice/attention if you feel unwell.  
P321 - Specific treatment (see section 4 on this SDS).  
P331 - Do NOT induce vomiting.  
P332+P313 - If skin irritation occurs: Get medical advice/attention.  
P362 - Take off contaminated clothing and wash it before reuse.  
P370+P378 - In case of fire: Use appropriate media (see section 5) to extinguish.  
P391 - Collect spillage.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

### 2.3. Other Hazards

Gasoline is a blend of several petroleum refinery streams to meet specifications set up in the United States by the American Society for Testing and Materials (ASTM D 439). This blend is predominantly a complex mixture of hydrocarbons that includes normal and branched alkanes, cycloalkanes, alkenes, and aromatics including benzene and Ethanol at up to 15.0% when the base gasoline is blended w/ Ethanol. Contains benzene, a regulated human carcinogen. Benzene has the potential to cause anemia and other blood diseases, including leukemia, after repeated and prolonged exposure. Exposure to light hydrocarbons in the same boiling range as this product has been associated in animal studies with systemic toxicity. See also Section 11 – Toxicological Information.

### 2.4. Unknown Acute Toxicity (GHS-US)

No data available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product Identifier	%	Classification (GHS-US)
Gasoline, motor fuel	(CAS No) 86290-81-5	85 - 100	Flam. Liq. 1, H224 Skin Irrit. 2, H315 Muta. 1B, H340 Carc. 1B, H350 Repr. 2, H361 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Ethyl Alcohol	(CAS No) 64-17-5	0 - 15	Flam Liq 2 H225

# Unleaded Gasoline

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Toluene	(CAS No) 108-88-3	<= 12	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 3, H412
Xylenes (o-, m-, p- isomers)	(CAS No) 1330-20-7	<= 12	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapor), H332 Skin Irrit. 2, H315 Asp. Tox. 1, H304 Aquatic Acute 2, H401
Hexane	(CAS No) 110-54-3	<= 5	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Benzene	(CAS No) 71-43-2	<= 3	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Muta. 1B, H340 Carc. 1A, H350 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
Cyclohexane	(CAS No) 110-82-7	<= 3	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Ethylbenzene	(CAS No) 100-41-4	<= 3	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation:vapor), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 3, H412
Naphthalene	(CAS No) 91-20-3	<= 3	Flam. Sol. 2, H228 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Carc. 2, H351 STOT SE 1, H370 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H-phrases: see section 16

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of First Aid Measures

**First-aid Measures General:** Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention.

# Unleaded Gasoline

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**First-aid Measures After Inhalation:** Remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm, quiet, and get medical attention.

**First-aid Measures After Skin Contact:** Thoroughly wash exposed area with soap and water. Remove contaminated clothing. Launder contaminated clothing before wearing. If skin irritation occurs: Get medical advice/attention.

**First-aid Measures After Eye Contact:** Flush with large amounts of water, lifting upper and lower lids occasionally. Remove contact lenses, if present and easy to do. Get medical attention.

**First-aid Measures After Ingestion:** DO NOT INDUCE VOMITING. Do not give liquids. If spontaneous vomiting occurs, lean victim forward to reduce the risk of aspiration. Keep person warm, quiet and get medical attention. Aspiration of material into the lungs due to vomiting can cause chemical pneumonia which can be fatal.

### 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms/Injuries:** Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. May cause cancer. May cause genetic defects. Suspected of damaging fertility or the unborn child. Causes damage to organs. Causes damage to organs through prolonged or repeated exposure.

**Symptoms/Injuries After Inhalation:** May cause drowsiness or dizziness. In high concentrations may cause narcotic effects. Symptoms may include dizziness, headache, nausea, loss of coordination, and asphyxiation.

**Symptoms/Injuries After Skin Contact:** Causes skin irritation. Repeated or prolonged skin contact may cause dermatitis and defatting.

**Symptoms/Injuries After Eye Contact:** Can cause severe eye irritation. Redness, pain, swelling, itching, burning, tearing, and blurred vision.

**Symptoms/Injuries After Ingestion:** The major health threat of ingestion occurs from the danger of aspiration (breathing) of liquid drops into the lungs, particularly from vomiting. Aspiration may result in chemical pneumonia (fluid in the lungs), severe lung damage, respiratory failure and even death.

**Chronic Symptoms:** May cause cancer. May cause genetic defects. Suspected of damaging fertility or the unborn child. Causes damage to organs. Causes damage to organs through prolonged or repeated exposure.

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

## SECTION 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Alcohol-resistant foam, carbon dioxide (CO<sub>2</sub>), dry chemical, water spray, fog.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. A heavy water stream may spread burning liquid. Water may be ineffective because it may not cool the material below its flash point.

### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Extremely flammable liquid and vapor.

**Explosion Hazard:** May form flammable/explosive vapor-air mixture. When mixed with air and exposed to an ignition source, flammable vapors can burn in the open or explode in confined spaces. Being heavier than air, vapors may travel long distances to an ignition source and flash back. Runoff to sewer may cause fire or explosion hazard. Material is highly volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point.

**Reactivity:** Reacts with strong oxidants causing fire and explosion hazard. Hazardous reactions may occur on contact with certain chemicals. Refer to incompatible materials.

### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion. Extinguish/cool from behind cover/unmanned monitors. Remove containers from fire area if this can be done without risk. Do not breathe fumes from fires or vapors from decomposition. Do not allow run-off from firefighting to enter drains or water courses.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Other Information:** Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Remove ignition sources. Use special care to avoid static electric charges. Keep away from heat, sparks, open flames, hot surfaces. No smoking. Avoid breathing (dust, vapor, mist, gas). Use only outdoors or in a well-ventilated area. Handle in accordance with good industrial hygiene and safety practice.

#### 6.1.1. For Non-emergency Personnel

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

# Unleaded Gasoline

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Emergency Procedures:** Evacuate unnecessary personnel.

## 6.1.2. For Emergency Responders

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel. Eliminate ignition sources. Stop leak if safe to do so. Ventilate area.

## 6.2. Environmental Precautions

Prevent entry to sewers and public waters.

## 6.3. Methods and Material for Containment and Cleaning Up

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Eliminate all ignition sources. Absorb and/or contain spill with inert material, then place in suitable container. Do not take up in combustible material such as: saw dust or cellulosic material. Use water spray to disperse vapors. If spilled directly onto the ground, remove sufficient soil to ensure material is fully recovered. Contact competent authorities after a spill. For small spill allow volatile portion to safely evaporate under controlled conditions. Allow sufficient time for vapors to completely clear. Check with LEL meter before cleaning up.

## 6.4. Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection. Concerning disposal elimination after cleaning, see item 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for Safe Handling

**Additional Hazards When Processed:** Handle empty containers with care because residual vapors are flammable.

**Precautions for Safe Handling:** Do not handle until all safety precautions have been read and understood. Take precautionary measures against static discharge. Use only non-sparking tools. Keep away from heat, sparks, open flames, hot surfaces. No smoking. Avoid all eye and skin contact and do not breathe vapor and mist. Use only outdoors or in a well-ventilated area. Use appropriate personal protection equipment (PPE). Never use welding or cutting torch on or near drum (even empty) because product and its residue can ignite explosively. Material is highly volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from materials handling point.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Wash hands and exposed areas thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Ground/bond container and receiving equipment. Use explosion-proof electrical, lighting, ventilating equipment. Container remains hazardous when empty. Continue to observe all precautions. Ensure all national/local regulations are observed. Do not allow smoking in areas of use or dispensing. Motors, fans, switches, and etc. in area of use or dispensing should be explosion proof. Ground containers when filling. Prevent all static and electric sparks.

**Storage Conditions:** Store containers in an upright position. Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep in fireproof place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up.

**Incompatible Products:** Strong acids. Strong bases. Strong oxidizers. Chlorine. Permanganates. Chromates.

### 7.3. Specific End Use(s)

No use is specified.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), or OSHA (PEL).

Ethyl Alcohol (Ethanol) (64-17-5)		
USA ACGIH	ACGIH STEL (ppm)	1000 ppm
USA OSHA	OSHA PEL (ppm)	1000 ppm
Benzene (71-43-2)		
USA ACGIH	ACGIH TWA (ppm)	0.5 ppm
USA ACGIH	ACGIH STEL (ppm)	2.5 ppm
USA ACGIH	ACGIH chemical category	Skin - potential significant contribution to overall exposure by the cutaneous route, Confirmed Human Carcinogen
USA NIOSH	NIOSH REL (TWA) (ppm)	0.1 ppm
USA NIOSH	NIOSH REL (STEL) (ppm)	1 ppm
USA IDLH	US IDLH (ppm)	500 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	1 ppm

# Unleaded Gasoline

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

		1 ppm
<b>USA OSHA</b>	OSHA PEL (STEL) (ppm)	5 ppm (see 29 CFR 1910.1028)
<b>USA OSHA</b>	OSHA PEL (Ceiling) (ppm)	25 ppm
<b>Cyclohexane (110-82-7)</b>		
<b>USA ACGIH</b>	ACGIH TWA (ppm)	100 ppm
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	1050 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (TWA) (ppm)	300 ppm
<b>USA IDLH</b>	US IDLH (ppm)	1300 ppm (10% LEL)
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	1050 mg/m <sup>3</sup>
<b>USA OSHA</b>	OSHA PEL (TWA) (ppm)	300 ppm
<b>Ethylbenzene (100-41-4)</b>		
<b>USA ACGIH</b>	ACGIH TWA (ppm)	20 ppm
<b>USA ACGIH</b>	ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (TWA) (ppm)	100 ppm
<b>USA NIOSH</b>	NIOSH REL (STEL) (mg/m <sup>3</sup> )	545 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (STEL) (ppm)	125 ppm
<b>USA IDLH</b>	US IDLH (ppm)	800 ppm (10% LEL)
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
<b>USA OSHA</b>	OSHA PEL (TWA) (ppm)	100 ppm
<b>Hexane (110-54-3)</b>		
<b>USA ACGIH</b>	ACGIH TWA (ppm)	50 ppm
<b>USA ACGIH</b>	ACGIH chemical category	Skin - potential significant contribution to overall exposure by the cutaneous route
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	180 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (TWA) (ppm)	50 ppm
<b>USA IDLH</b>	US IDLH (ppm)	1100 ppm (10% LEL)
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
<b>USA OSHA</b>	OSHA PEL (TWA) (ppm)	500 ppm
<b>Naphthalene (91-20-3)</b>		
<b>USA ACGIH</b>	ACGIH TWA (ppm)	10 ppm
<b>USA ACGIH</b>	ACGIH chemical category	Skin - potential significant contribution to overall exposure by the cutaneous route, Confirmed Animal Carcinogen with Unknown Relevance to Humans
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (TWA) (ppm)	10 ppm
<b>USA NIOSH</b>	NIOSH REL (STEL) (mg/m <sup>3</sup> )	75 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (STEL) (ppm)	15 ppm
<b>USA IDLH</b>	US IDLH (ppm)	250 ppm
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
<b>USA OSHA</b>	OSHA PEL (TWA) (ppm)	10 ppm
<b>Toluene (108-88-3)</b>		
<b>USA ACGIH</b>	ACGIH TWA (ppm)	20 ppm
<b>USA ACGIH</b>	ACGIH chemical category	Not Classifiable as a Human Carcinogen
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (TWA) (ppm)	100 ppm
<b>USA NIOSH</b>	NIOSH REL (STEL) (mg/m <sup>3</sup> )	560 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (STEL) (ppm)	150 ppm
<b>USA IDLH</b>	US IDLH (ppm)	500 ppm
<b>USA OSHA</b>	OSHA PEL (TWA) (ppm)	200 ppm
<b>USA OSHA</b>	OSHA PEL (Ceiling) (ppm)	300 ppm
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>		
<b>USA ACGIH</b>	ACGIH TWA (ppm)	100 ppm
<b>USA ACGIH</b>	ACGIH STEL (ppm)	150 ppm

# Unleaded Gasoline

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>USA ACGIH</b>	ACGIH chemical category	Not Classifiable as a Human Carcinogen
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
<b>USA OSHA</b>	OSHA PEL (TWA) (ppm)	100 ppm
<b>Gasoline, motor fuel (86290-81-5)</b>		
<b>USA ACGIH</b>	ACGIH TWA (ppm)	300 ppm
<b>USA ACGIH</b>	ACGIH STEL (ppm)	500 ppm
<b>USA ACGIH</b>	ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans

## 8.2. Exposure Controls

### Appropriate Engineering Controls

: Use explosion-proof equipment. Proper grounding procedures to avoid static electricity should be followed. Gas detectors should be used when flammable gases/vapors may be released. Ensure adequate ventilation, especially in confined areas. Have written confined space and tank entry procedures. Never allow tank entry without checking OXYGEN AND VAPOR levels. Use safety harness and safety line on person entering a tank. Stand-by person required with protective equipment available. Ensure all national/local regulations are observed.

### Personal Protective Equipment

: Where splashing is possible: Safety glasses with side shields. Face shield. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.



### Materials for Protective Clothing

: Chemically resistant materials and fabrics. Wear fire/flame resistant/retardant clothing.

### Hand Protection

: Wear chemically resistant protective gloves such as neoprene or nitrile.

### Eye Protection

: No special eye protection is normally required. Where splashing is possible, wear safety glasses with sideshields and faceshield.

### Skin and Body Protection

: Wear suitable protective clothing.

### Respiratory Protection

: Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

### Thermal Hazard Protection

: When working with hot material, use suitable thermally protective clothing.

### Other Information

: When using, do not eat, drink, or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

<b>Physical State</b>	: Liquid
<b>Appearance</b>	: Clear mobile liquid. Gasoline is colored with various dyes for specific type recognition.
<b>Odor</b>	: Characteristic odor recognizable at about 0.4 – 0.7 PPM in air.
<b>Odor Threshold</b>	: No data available
<b>pH</b>	: No data available
<b>Evaporation Rate</b>	: Slower than ether
<b>Melting Point</b>	: No data available
<b>Freezing Point</b>	: No data available
<b>Boiling Point</b>	: 70 - 435 °F (21.11 - 223.89 °C)
<b>Flash Point</b>	: -40 - 50 °F (-40 - 45.56 °C)
<b>Auto-ignition Temperature</b>	: No data available
<b>Decomposition Temperature</b>	: No data available
<b>Flammability (solid, gas)</b>	: Flammable liquid
<b>Vapor Pressure</b>	: 7 - 15 (Reid Vapor Pressure @ 100°F)
<b>Relative Vapor Density</b>	: 3 - 4 (AIR=1)
<b>Relative Density</b>	: No data available
<b>Specific Gravity at 60 °F</b>	: 0.7 - 0.78 (water=1)
<b>Solubility</b>	: Insoluble in water.
<b>Partition Coefficient: N-Octanol/Water</b>	: 2 – 7 (as per P)

# Unleaded Gasoline

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Viscosity	: No data available
Explosive Properties	: Product is not explosive, however, formation of explosive air-vapor mixture is possible.
Lower Flammable Limit	: 1.4 %
Upper Flammable Limit	: 7.6 %
Percent Volatile By Volume	: 100 %
Explosive Limits	: Lower to 1.4%

9.2. Other Information No additional information available

## SECTION 10: STABILITY AND REACTIVITY

- 10.1. **Reactivity:** Reacts with strong oxidants causing fire and explosion hazard. Hazardous reactions may occur on contact with certain chemicals. Refer to incompatible materials.
- 10.2. **Chemical Stability:** Extremely flammable liquid and vapor. May form flammable/explosive vapor-air mixture.
- 10.3. **Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. **Conditions to Avoid:** Direct sunlight. Extremely high or low temperatures. Sources of ignition. Incompatible materials.
- 10.5. **Incompatible Materials:** Strong acids. Strong bases. Strong oxidizers. Chlorine. Permanganates. Chromates.
- 10.6. **Hazardous Decomposition Products:** Thermal decomposition generates: May release flammable gases. Carbon oxides (CO, CO<sub>2</sub>). Hydrocarbons.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information On Toxicological Effects

Acute Toxicity: Not classified

<b>Ethyl Alcohol (Ethanol) (64-17-5)</b>	
LC50 Inhalation Rat	>20,000 ppm/10hr
<b>Benzene (71-43-2)</b>	
LD50 Oral Rat	3306 mg/kg
LD50 Dermal Rabbit	> 8200 mg/kg
LC50 Inhalation Rat	44.66 mg/l/4h
<b>Cyclohexane (110-82-7)</b>	
LD50 Oral Rat	12705 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	13.9 mg/l/4h
<b>Ethylbenzene (100-41-4)</b>	
LD50 Oral Rat	3500 mg/kg
LD50 Dermal Rabbit	15400 mg/kg
LC50 Inhalation Rat	17.2 mg/l/4h (Exposure time: 4 h)
<b>Hexane (110-54-3)</b>	
LD50 Oral Rat	25 g/kg
LD50 Dermal Rabbit	3000 mg/kg
LC50 Inhalation Rat	48000 ppm/4h
<b>Naphthalene (91-20-3)</b>	
LD50 Oral Rat	533 - 710 mg/kg
LD50 Dermal Rabbit	1120 mg/kg
LC50 Inhalation Rat	> 340 mg/m <sup>3</sup> (Exposure time: 1 h)
<b>Toluene (108-88-3)</b>	
LD50 Oral Rat	5580 mg/kg
LD50 Dermal Rabbit	12000 mg/kg
LC50 Inhalation Rat	12.5 mg/l/4h
ATE (Vapors)	25.70 mg/l/4h
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 4350 mg/kg
LC50 Inhalation Rat	29.08 mg/l/4h
LC50 Inhalation Rat	6247 ppm/4h (species: Sprague-Dawley)
ATE (Dermal)	1,100.00 mg/kg body weight



# Unleaded Gasoline

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ATE (Gases)	6,247.00 ppmV/4h
ATE (Vapors)	11.00 mg/l/4h
<b>Gasoline, motor fuel (86290-81-5)</b>	
LD50 Oral Rat	92 g/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	> 5.2 mg/l/4h

**Skin Corrosion/Irritation:** Causes skin irritation.

**Serious Eye Damage/Irritation:** Not classified

**Respiratory or Skin Sensitization:** Not classified

**Germ Cell Mutagenicity:** May cause genetic defects.

**Carcinogenicity:** May cause cancer.

<b>Benzene (71-43-2)</b>	
IARC group	1
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity, Known Human Carcinogens.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
OSHA Specifically Regulated Carcinogen List	In OSHA Specifically Regulated Carcinogen list.

<b>Ethylbenzene (100-41-4)</b>	
IARC group	2B
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.

<b>Naphthalene (91-20-3)</b>	
IARC group	2B
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity, Reasonably anticipated to be Human Carcinogen.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.

<b>Toluene (108-88-3)</b>	
IARC group	3

<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
IARC group	3

<b>Gasoline, motor fuel (86290-81-5)</b>	
IARC group	2B
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.

**Reproductive Toxicity:** Suspected of damaging fertility or the unborn child.

**Specific Target Organ Toxicity (Single Exposure):** Causes damage to organs. May cause drowsiness or dizziness.

**Specific Target Organ Toxicity (Repeated Exposure):** Causes damage to organs through prolonged or repeated exposure.

**Aspiration Hazard:** May be fatal if swallowed and enters airways.

**Symptoms/Injuries After Inhalation:** May cause drowsiness or dizziness. In high concentrations may cause narcotic effects. Symptoms may include dizziness, headache, nausea and loss of coordination, and asphyxiation.

**Symptoms/Injuries After Skin Contact:** Causes skin irritation. Repeated or prolonged skin contact may cause dermatitis and defatting.

**Symptoms/Injuries After Eye Contact:** Can cause severe eye irritation. Redness, pain, swelling, itching, burning, tearing, and blurred vision.

**Symptoms/Injuries After Ingestion:** The major health threat of ingestion occurs from the danger of aspiration (breathing) of liquid drops into the lungs, particularly from vomiting. Aspiration may result in chemical pneumonia (fluid in the lungs), severe lung damage, respiratory failure and even death.

**Chronic Symptoms:** May cause cancer. May cause genetic defects. Suspected of damaging fertility or the unborn child. Causes damage to organs. Causes damage to organs through prolonged or repeated exposure.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

Ecology - General : Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

<b>Benzene (71-43-2)</b>	
LC50 Fish 1	10.7 - 14.7 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	8.76 - 15.6 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC 50 Fish 2	5.3 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])

# Unleaded Gasoline

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>EC50 Daphnia 2</b>	10 mg/l (Exposure time: 48 h - Species: Daphnia magna)
<b>Cyclohexane (110-82-7)</b>	
<b>LC50 Fish 1</b>	3.96 - 5.18 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
<b>EC50 Daphnia 1</b>	0.9 mg/l
<b>LC 50 Fish 2</b>	23.03 - 42.07 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
<b>Ethylbenzene (100-41-4)</b>	
<b>LC50 Fish 1</b>	11.0 - 18.0 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
<b>EC50 Daphnia 1</b>	1.8 - 2.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
<b>LC 50 Fish 2</b>	4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static])
<b>Hexane (110-54-3)</b>	
<b>LC50 Fish 1</b>	2.1 - 2.98 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
<b>EC50 Daphnia 1</b>	3.88 mg/l
<b>Naphthalene (91-20-3)</b>	
<b>LC50 Fish 1</b>	5.74 - 6.44 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
<b>EC50 Daphnia 1</b>	2.16 mg/l (Exposure time: 48 h - Species: Daphnia magna)
<b>LC 50 Fish 2</b>	1.6 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
<b>EC50 Daphnia 2</b>	1.96 mg/l (Exposure time: 48 h - Species: Daphnia magna [Flow through])
<b>Toluene (108-88-3)</b>	
<b>LC50 Fish 1</b>	15.22 (15.22 - 19.05) mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
<b>EC50 Daphnia 1</b>	5.46 (5.46 - 9.83) mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
<b>LC 50 Fish 2</b>	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
<b>EC50 Daphnia 2</b>	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
<b>NOEC chronic crustacea</b>	0.74 mg/l (Ceriodaphnia dubia)
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
<b>LC50 Fish 1</b>	3.3 mg/l
<b>EC50 Daphnia 1</b>	3.82 mg/l (Exposure time: 48 h - Species: water flea)
<b>LC 50 Fish 2</b>	2.661 (2.661 - 4.093) mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
<b>EC50 Daphnia 2</b>	0.6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris)

### 12.2. Persistence and Degradability

<b>Unleaded Gasoline</b>	
<b>Persistence and Degradability</b>	Not established.

### 12.3. Bioaccumulative Potential

<b>Unleaded Gasoline</b>	
<b>Bioaccumulative Potential</b>	Not established.
<b>Benzene (71-43-2)</b>	
<b>BCF fish 1</b>	3.5 - 4.4
<b>Log Pow</b>	1.83
<b>Cyclohexane (110-82-7)</b>	
<b>Log Pow</b>	3.44
<b>Ethylbenzene (100-41-4)</b>	
<b>BCF fish 1</b>	15
<b>Log Pow</b>	3.118
<b>Naphthalene (91-20-3)</b>	
<b>BCF fish 1</b>	30 - 430
<b>Log Pow</b>	3.3 (at 20 °C)
<b>Toluene (108-88-3)</b>	
<b>Log Pow</b>	2.65
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
<b>BCF fish 1</b>	0.6 (0.6 - 15)
<b>Log Pow</b>	2.77 - 3.15

# Unleaded Gasoline

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**12.4. Mobility in Soil** No additional information available

**12.5. Other Adverse Effects**

**Other Information** : Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

**13.1. Waste treatment methods**

**Sewage Disposal Recommendations:** Do not empty into drains; dispose of this material and its container in a safe way.

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, and international regulations.

**Additional Information:** EPA Hazardous Waste Number: D001 (Ignitability).

**Ecology – Waste Materials:** Hazardous waste due to toxicity.

## SECTION 14: TRANSPORT INFORMATION

**14.1. In Accordance with DOT**

**Gasoline with 0-10% ethanol**

**Proper Shipping Name** : GASOLINE  
**Hazard Class** : 3  
**Identification Number** : UN1203  
**Label Codes** : 3  
**Packing Group** : II  
**Marine Pollutant** : No  
**ERG Number** : 128



**Gasoline with more than 10% ethanol**

**Proper Shipping Name** : ETHANOL AND GASOLINE MIXTURE  
**Hazard Class** : 3  
**Identification Number** : UN3475  
**Label Codes** : 3  
**Packing Group** : II  
**Marine Pollutant** : No  
**ERG Number** : 128



**14.2. In Accordance with IMDG**

**Gasoline with 0-10% ethanol**

**Proper Shipping Name** : GASOLINE  
**Hazard Class** : 3  
**Identification Number** : UN1203  
**Packing Group** : II  
**Label Codes** : 3  
**EmS-No. (Fire)** : F-E  
**EmS-No. (Spillage)** : S-E  
**Marine Pollutant** : Marine pollutant



**Gasoline with more than 10% ethanol**

**Proper Shipping Name** : ETHANOL AND GASOLINE MIXTURE  
**Hazard Class** : 3  
**Identification Number** : UN3475  
**Packing Group** : II  
**Label Codes** : 3  
**EmS-No. (Fire)** : F-E  
**EmS-No. (Spillage)** : S-E  
**Marine Pollutant** : Marine pollutant



# Unleaded Gasoline

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## 14.3. In Accordance with IATA

### Gasoline with 0-10% ethanol

Proper Shipping Name : GASOLINE  
Packing Group : II  
Identification Number : UN1203  
Hazard Class : 3  
Label Codes : 3  
ERG Code (IATA) : 3H



### Gasoline with more than 10% ethanol

Proper Shipping Name : ETHANOL AND GASOLINE MIXTURE  
Packing Group : II  
Identification Number : UN3475  
Hazard Class : 3  
Label Codes : 3  
ERG Code (IATA) : 3H



## SECTION 15: REGULATORY INFORMATION

### 15.1 US Federal Regulations

<b>Unleaded Gasoline</b>	
<b>SARA Section 311/312 Hazard Classes</b>	Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard
<b>Benzene (71-43-2)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on United States SARA Section 313	
<b>RQ (Reportable quantity, section 304 of EPA's List of Lists)</b>	10 lb
<b>SARA Section 311/312 Hazard Classes</b>	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
<b>SARA Section 313 - Emission Reporting</b>	0.1 %
<b>Cyclohexane (110-82-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on United States SARA Section 313	
<b>EPA TSCA Regulatory Flag</b>	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
<b>SARA Section 313 - Emission Reporting</b>	1.0 %
<b>Ethylbenzene (100-41-4)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on United States SARA Section 313	
<b>RQ (Reportable quantity, section 304 of EPA's List of Lists)</b>	1000 lb
<b>SARA Section 313 - Emission Reporting</b>	0.1 %
<b>Hexane (110-54-3)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on United States SARA Section 313	
<b>SARA Section 313 - Emission Reporting</b>	1.0 %
<b>Naphthalene (91-20-3)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on United States SARA Section 313	
<b>EPA TSCA Regulatory Flag</b>	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.

# Unleaded Gasoline

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>RQ (Reportable quantity, section 304 of EPA's List of Lists)</b>	100 lb
<b>SARA Section 313 - Emission Reporting</b>	0.1 %
<b>Toluene (108-88-3)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on United States SARA Section 313	
<b>RQ (Reportable quantity, section 304 of EPA's List of Lists)</b>	1000 lb
<b>SARA Section 313 - Emission Reporting</b>	1.0 %
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on United States SARA Section 313	
<b>RQ (Reportable quantity, section 304 of EPA's List of Lists)</b>	100 lb
<b>SARA Section 311/312 Hazard Classes</b>	Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard
<b>SARA Section 313 - Emission Reporting</b>	1.0 %

## 15.2 US State Regulations

<b>Benzene (71-43-2)</b>	
<b>U.S. - California - Proposition 65 - Carcinogens List</b>	WARNING: This product contains chemicals known to the State of California to cause cancer.
<b>U.S. - California - Proposition 65 - Developmental Toxicity</b>	WARNING: This product contains chemicals known to the State of California to cause birth defects.
<b>U.S. - California - Proposition 65 - Reproductive Toxicity - Male</b>	WARNING: This product contains chemicals known to the State of California to cause (Male) reproductive harm.
<b>Ethylbenzene (100-41-4)</b>	
<b>U.S. - California - Proposition 65 - Carcinogens List</b>	WARNING: This product contains chemicals known to the State of California to cause cancer.
<b>Naphthalene (91-20-3)</b>	
<b>U.S. - California - Proposition 65 - Carcinogens List</b>	WARNING: This product contains chemicals known to the State of California to cause cancer.
<b>Toluene (108-88-3)</b>	
<b>U.S. - California - Proposition 65 - Developmental Toxicity</b>	WARNING: This product contains chemicals known to the State of California to cause birth defects.
<b>U.S. - California - Proposition 65 - Reproductive Toxicity - Female</b>	WARNING: This product contains chemicals known to the State of California to cause (Female) reproductive harm.
<b>Benzene (71-43-2)</b>	
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances U.S. - Pennsylvania - RTK (Right to Know) List	
<b>Cyclohexane (110-82-7)</b>	
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List	
<b>Ethylbenzene (100-41-4)</b>	
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List	
<b>Hexane (110-54-3)</b>	
U.S. - Massachusetts - Right To Know List	

# Unleaded Gasoline

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
<b>Naphthalene (91-20-3)</b> U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List
<b>Toluene (108-88-3)</b> U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b> U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List
<b>Gasoline, motor fuel (86290-81-5)</b> U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

<b>Revision Date</b>	: 06/28/2016
<b>Other Information</b>	: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200. This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

### GHS Full Text Phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation:vapor)	Acute toxicity (inhalation:vapor) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 1A	Carcinogenicity Category 1A
Carc. 1B	Carcinogenicity Category 1B
Carc. 2	Carcinogenicity Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 1	Flammable liquids Category 1
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Flam. Sol. 2	Flammable solids Category 2
Muta. 1B	Germ cell mutagenicity Category 1B
Repr. 2	Reproductive toxicity Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3

# Unleaded Gasoline

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H224	Extremely flammable liquid and vapor
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H228	Flammable solid
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H361	Suspected of damaging fertility or the unborn child
H370	Causes damage to organs
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

### NFPA Health Hazard


: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

### NFPA Fire Hazard

: 3 - Liquids and solids that can be ignited under almost all ambient conditions.

### NFPA Reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



### HMIS III Rating

#### Health

: 2 Moderate Hazard - Temporary or minor injury may occur

#### Flammability

: 3 Serious Hazard

#### Physical

: 0 Minimal Hazard

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

SDS US (GHS HazCom)